

Blitzbinder®, round															
Made of branded polyethylene. Universal tie. Worldwide patent. Can be reopened over and over.															
Form A							Form B								
Article No.	"L" in mm	"D" in mm	Tensile strength in N, min.	Form	Natural	Red	Special colours	Article No.	"L" in mm	"D" in mm	Tensile strength in N, min.	Form	Natural	Red	Special colours
ABV 212	120	3.5	130	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	ABVS 230	290	8.7	420	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
ABW 214	140	3.9	170	A	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	ABV 232	320	4.4	230	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
ABV 218	180	3.5	150	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	ABV 250	500	5.7	250	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
ABV 224	240	3.9	180	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	ABVS 270	665	6.6	370	B	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

The Allplastik-Blitzbinder® quick fasteners made of premium quality polyethylene have a special closure which, when combined with a round profile, guarantees maximum strength and reliable closing and can also be opened again at any time. In addition to its function as a fastener, the dual closure design of the Allplastik-Blitzbinder® quick fasteners allow a hanging loop to be formed.

- Material: Polyethylene
- Design: ABV (2 engaging holes), ABW (1 engaging hole), ABVS (extra strong version)
- Colour: red, natural, blue, yellow, green, black, brown, purple, orange, pink, olive green
- Length: 120 to 665 mm
- Printing or laser engraving: possible
- Temperature resistance: from - 40°C to + 70°C
- Extraction force: 13 to 42 daN (kg)
- The raw materials from which the Allplastik-Blitzbinder® quick fasteners are made are FDA-compliant and comply with the following EU directives: 1935/2004/EU, 2023/2006/EU and as amended, 10/2011/EU (contact with foodstuffs) as amended. 94/62/EU (packaging waste) and as amended concerning the defined limits of heavy metals. 2002/95/EU (RoHS) and 2011/65/EU as amended. 1907/2006/EU (REACH).